



DIMENSIONS							UNIT : mm	
N D	A	H1	H2	t	C	D	4-φh	
15A	130	70	334	16	70	95	4-15	
20A	150	75	334	18	75	100	4-15	
25A	160	75	334	18	90	125	4-19	
32A	200	97	339	20	100	135	4-19	
40A	200	97	339	20	105	140	4-19	

NOMINAL PRESSURE : 10 kg/cm<sup>2</sup>

ACTUATOR SPECIFICATION

Enclosure	IP54 (DIN40050, IEC144)
Power supply	24V AC ±10%
Rated current	0.069 A
Nominal force	2000N
Nominal stroke	20mm
Operating time	55 sec
Manual override	Hand/Auto Decutching mechanism
Condenser	33 ?
Conduit	PF ½" TAP

6	ACTUATOR	20P/35P	1	
5	STEM	STS304	1	
4	PACKING	VITON	1	
3	DISC	STS304	1	
2	COVER	FC20	1	
1	BODY	FC20	1	
P.N.D.	PART NAME	MATERIAL	Q'TY	REMARK
△	FIRST ISSUE	02.05.22		
REV NO	REVISION NOTE	DATE	DRW	APP

2-WAY CONTROL VALVE

FILE NAME	JSV-1F-1540			
DWG	DWG	DWG	DWG	SCALE : N/S
				DWG NO
				JSV-002



제 이 에 스 밸브