



ACTUATOR SPECIFICATION

Enclosure	IP54 (DIN40050, IEC144)
Power supply	24V AC $\pm 10\%$
Rated current	0.069/86 A
Nominal force	2000/3500/5500N
Nominal stroke	20mm/40mm
Operating time	55/105/70 sec
Manual override	Hand/Auto Declutching mechanism
Condenser	33/56 ?
Conduit	PF 1/2" TAP

DIMENSIONS										UNIT : mm
N D	A	H1	H2	t	C	D	n-phi h			
50A	230	138	339	20	120	155	4-19			
65A	290	168	360	22	140	175	4-19			
80A	310	176	360	22	150	185	8-19			
100A	350	193	421	24	175	210	8-19			
125A	400	233	462	24	210	250	8-23			
150A	480	270	478	26	240	280	8-23			

NOMINAL PRESSURE : 10 kg/cm²

REV NO	REVISION NOTE	DATE	DRW	APP
6	ACTUATOR	20P/35P	1	
5	STEM	STS304	1	
4	PACKING	VITON	1	
3	DISC	STS304	1	
2	COVER	FC20	1	
1	BODY	FC20	1	

P.N.D.	PART NAME	MATERIAL	Q'TY	REMARK
△	FIRST ISSUE	02.05.22		

2-WAY CONTROL VALVE

FILE NAME	JSV-1F-50150			
DWG	DWG	DWG	DWG	SCALE : N/S
				DWG NO
				JSV-003



제 이 에 스 밸 브