



ACTUATOR SPECIFICATION

Enclosure	IP54 (DIN40050, IEC144)
Power supply	24V AC ±10%
Rated current	0.069/0.86 A
Nominal force	2000/3500/5500
Nominal stroke	20mm/40mm
Operating time	55/105/70 sec
Manual override	Hand/Auto Decutching mechanism
Condenser	33/56 ?
Conduit	PF 1/2 TAP

DIMENSIONS										UNIT : mm	
N	D	A	H1	H2	t	C	D	n-φh			
15A	130	69	364	16	70	95	4-15				
20A	150	73	364	18	75	100	4-15				
25A	160	73	364	18	90	125	4-19				
32A	202	97	357	20	100	135	4-19				
40A	202	97	357	20	105	140	4-19				
50A	230	122	396	20	120	155	8-19				
65A	290	132	444	22	140	175	8-19				
80A	310	156	456	24	160	200	8-23				
100A	350	189	476	26	185	225	8-23				
125A	400	190	523	26	225	270	8-25				
150A	480	210	546	28	260	305	12-25				

NOMINAL PRESSURE : 10 kg/cm<sup>2</sup>

REV NO	REVISION NOTE	DATE	DRW	APP
1	FIRST ISSUE	02.05.22		

2-WAY CONTROL VALVE

FILE NAME	JSV-2F-15150			
DWG	DWG	DWG	DWG	SCALE : N/S
				DWG NO
				JSV-004



제 이 에 스 밸 브