



ACTUATOR SPECIFICATION

Enclosure	IP54 (DIN40050, IEC144)
Power supply	24V AC ±10%
Rated current	0.069/86 A
Nominal force	2000/3500/5500N
Nominal stroke	20mm/40mm
Operating time	55/105/70 sec
Manual override	Hand/Auto Declutching mechanism
Condenser	33/56 ?
Conduit	PF 1/2" TAP

DIMENSIONS										UNIT : mm	
N D	A	H1	H2	t	C	D	n-phi_h				
15A	130	130	334	16	70	95	4-15				
20A	150	130	334	18	75	100	4-15				
25A	160	130	334	18	90	125	4-19				
32A	200	163	339	20	100	135	4-19				
40A	200	163	339	20	105	140	4-19				
50A	230	118	339	20	120	155	4-19				
65A	290	146	360	22	140	175	4-19				
80A	310	155	360	22	150	185	8-19				
100A	350	180	421	24	175	210	8-19				
125A	400	200	462	24	210	250	8-23				
150A	480	280	478	26	240	280	8-23				

NOMINAL PRESSURE : 10 kg/ cm<sup>2</sup>

6	ACTUATOR	20P/35P	1	
5	STEM	STS304	1	
4	PACKING	VITDN	1	
3	DISC	STS304	1	
2	COVER	FC20	1	
1	BDDY	FC20	1	
P.ND.	PART NAME	MATERIAL	Q'TY	REMARK
△	FIRST ISSUE	02.05.22		
REV NO	REVISION NOTE	DATE	DRW	APP

3-WAY CONTROL VALVE

FILE NAME		JSV-3F-15150			
DWG	DWG	DWG	DWG	SCALE : N/S	DWG NO
					JSV-006



제이에스밸브