



DIMENSIONS										UNIT : mm	
ND	A	B	H	H1	n- $\phi$ h	$\phi$ C	$\phi$ D	L			
15A	121	173	100	147	4-15	70	95	147			
20A	121	173	105	147	4-15	75	100	152			
25A	121	173	120	147	4-19	90	125	172			
32A	121	173	130	147	4-19	100	135	177			
40A	121	173	130	147	4-19	105	140	194			
50A	176	237	140	192	4-19	120	155	215			
65A	176	237	150	192	4-19	140	175	262			
80A	176	237	155	192	8-19	150	185	271			
100A	230	290	170	248	8-19	175	210	300			
125A	230	290	190	248	8-23	210	250	360			
150A	230	290	200	248	8-23	240	280	360			

FLANGE RATING : JIS 10K

8	ACTUATOR	AC4C	1	
7	MANUAL OVERRIDE	SS400	1	
6	STEM	C-PVC	1	
5	O-ring	EPDM	1	
4	BOLT	SS41 (COATED)	1	
3	SEAT	PTFE	1	
2	BALL	C-PVC	1	
1	BODY	C-PVC	1	
P.N.O.	PART NAME	MATERIAL	Q'TY	REMARK
	FIRST ISSUE	09.02.10		
REV NO	REVISION NOTE	DATE	DRW	APP

ELECTRIC PVC BALL VALVE

SIZE 15-150A

DWG	DES'N	CHK'D	APP'D	SCALE	N/S
				DWG NO	
				PCM-013	



제이에스밸브